

MEASUREMENTS

HEIGHT	180 cm.
WIDTH	72 cm.
DEPTH	82 cm.
WEIGHT	130 kilos.



VERSIONS	Instant, Espresso.
CANISTERS	5 canisters in the Espresso. 7 canisters in the Instant.
SELECTIONS	22.
CUPS	800.
MATERIAL	Structure in painted sheet metal. Canisters in alimentary polypropilene.
DISPLAY	Graphic; one can use all graphic fonts, graphic icons and program 8 different spots. The display shows the commands contemporaneously in 2 different languages (of your choice). Programmable stand-by.
ILLUMINATION	Led which lights on the prepared drink. Retro illuminated panels.
KEYPAD	Direct selection of the drink and sugar dosage with Touch Sensor keypad. Keys with acoustic warning.
STIRRER HOLDER	Can be regulated for stirrers of 90 and 105 mm.
CUP RELEASE	Extractable module for easier cleaning and inspection.
BOILER	Electronic control of the boiler temperature; Security valve.
EXTRACTOR	For eliminating internal humidity (2 speeds).
PUMP	Vibration electromagnet of 60W.
SECURITY	Device with anti-flood system. Security and anti-boiling thermostat for soluble boilers. Components at 24V. Boiler security valve.
ACCESSORIES AND OPTIONALS	Autonomous self-feeding kit (2 x 25 litre tanks). SD card reader. Logic board programmer (to copy and quickly transfer the functioning parameters from one distributor to another). "No cup" option. Cold version. Double executive.

TECHNOLOGY

EVA-DTS.
GPE-DATA (usable with Excel type program).
Software which can be updated by PC or by logic board programmer.
Data logger with detailed information on every single vend.
Programmable stand-by with clock also weekly based.

**ABSORBED POWER
AND POWER SUPPLY**

V230 +/- 10%.
Hz 50/60.
1, 6 Kw for the boiler to reach its temperature (in a few minutes).
60W standard consumption.

PAYMENT SYSTEMS

Executive protocol.
MDB protocol.
Direct parallel coin mechanism.

DESIGN

Italian Style by Architects Floris & Giommi.